





Edge

Versatility For Today's Collection Needs

- 95, 65, 45, 35 and 25 gallon options
- Unique, contoured body is optimized for automated lifting equipment
- Patented molded-in feature at sides of cart for added gripping power
- Contoured lid reduces warp and water entrapment

- Injection-molded HDPE plastic allows for intricate molded-in detail
- Durable "double-pinned" lid attachment
- Large comfortable handles with extra clearance provide ease when handling cart
- Lift lip across front and around front corners increases opening convenience

Easy-grip Lid attachments are handles cylindrical-shaped and provide safe double-ribbed, creating maneuverability a robust attachment to container body Secure fitting lid helps to prevent rain, insects, and vermin from entering container Molded-in feature on four sides add gripping power at time of collection 25 and 45 gallons include a "fully assembled" option, making delivery and UV resistant distribution efforts plastic for long quick and easy with term exposure Wear strips at bottom of no assembly upon to sunlight container provide protection arrival against abrasive use

All Edge containers are ANSI compliant.

Features

- Designed to allow for composition of up to 98% post-consumer material
- · Empty container sustains winds averaging 43-63 mph
- · Zinc-plated hardware protects against rust and corrosion
- 25, 35, and 45 gallon Edge products are fully sealed to collect organic food waste





Nestable 25 and 45 gallon provides the option for containers to be shipped with no additional assembly required.



Cart Options

- Available in bib or comb (bibless or Euro) option[†]
- · Available with metal, plastic, or no lift bar option*
- Available in unassembled and stacked or fully assembled and nested**

[†]Not all models are available in comb-style (bibless or Euro). *Some models only available with plastic lift bar. **Nestable option only available in 25 and 45 gallons.

Collection With The 25 Gallon

Otto's 25 gallon Edge cart suits existing collection systems. Use fully-automated gripping arms or a semi-automated lifter using a proprietary adapter plate.







Semi-Automated Rear Load With Adapter Plate



on the 35 gallon facilitates the need for a fully sealed container solution. Ideally suited for food waste collection.

Molded Recess at bottom allows foot to be

placed directly on axle, providing leverage for



Customize Your Cart

- · Provide instructions to users with in-mold labeling
- Brand your cart with hot stamps on sides, front, or lid. ColorFUSE technology available on sides and lid
- Sequential serial numbers
- RFID tag or barcode
- Lid options include lid with circular opening, slot lid for paper disposal, and locking lid for added security



Secure-Fitting Lid keeps pests and precipitation away from container contents.

Lid Contour is engineered to allow for ample drainage

during time of precipitation.

Wheel Options

Wheels: 10" wheels are standard on the 65 and 95. 8" wheels are standard on the 25, 35 and 45, 95 gallon also available with 12" wheels. Popular wheel options are shown here. Other options are available upon request.

25, 35 & 45 Gallon Wheel Options:



65 & 95 Gallon Wheel Options:



Wheel options may change without notice.

Available Colors

The Edge container is available in 8 standard colors. Custom colors available upon request.



Black - 60 Dark Gray - 50 Light Gray - 57 Brown - 63

Colors as shown in this document may differ slightly from the actual product.

maneuvering.





95

65



45

35



Cart Specifications MODEL HEIGHT WIDTH DEPTH LOAD RATING° MSD-95 E 45³/8" **27** ¹/₂" **33** ¹/₄" 338 LBS. 42 3/8" 25 ¹/8" **29** ¹/₂" MSD-65 E 230 LBS. MSD-45 E **39** 1/5" 22 ³/₅" 27²/₅" 160 LBS. MSD-35 E 38" **19** ⁴/₅" 24 4/5" 122.5 LBS. 28 4/5" **19** 4/5" 24⁴/₅" MSD-25 E 88 LBS.

Cart specifications vary slightly based on product mold. °A.N.S.I. maximum load rating is 3.5 lbs. per gallon.

Shipping Information				
MODEL	ASSEMBLY WEIGHT	STACKING	LTL STACKING	T/L QTY (53' TRUCK)
MSD-95 E	40 LBS.	8 HIGH	7 HIGH	504
MSD-65 E	35 LBS.	9 HIGH	8 HIGH	720
MSD-45 E (N)	23 LBS.	8 HIGH	8 HIGH	672
MSD-45 E (U)	23 LBS.	10 HIGH	10 HIGH	760
MSD-35 E	19.25 LBS.	10 HIGH	9 HIGH	940
MSD-25 E (N)	17 LBS.	9 HIGH	9 HIGH	954
MSD-25 E (U)	17 LBS.	12 HIGH	12 HIGH	1,272

Shipping information varies slightly based on product mold and mold location. (N) represents fully-assembled, nested

containers. (U) represents unassembled, stacked containers.

Otto Environmental Systems North America, Inc.

12700 General Drive, Charlotte, North Carolina 28273 800-227-5885 • info@otto-usa.com • otto-usa.com

© Otto Environmental Systems North America, Inc.



