

 ∇ Newly designed raised

packer head cylinders

- V Easy rear access for cleaning
- ▼ Improved cylinder/pin access
- ▼ Interchangeable with most existing RJ-250SC applications
- Great for waste with high liquid content



The Worldwide Compaction Leader

Marathon[®] Equipment is known throughout the world as one the leading manufacturers of quality on-site waste compaction products. The RamJet[®] brand has been the industry standard for quality and innovation for more than 50 years, and includes stationary and self-contained compactors, compaction containers, apartment and high-rise compactors, pre-crushers, transfer systems, and a wide array of options for virtually any application.







Perfect for:



The **SC**² is perfect for weekly volumes of more than 100 cubic yards of wet or general waste materials.

Why Marathon[®] Equipment Is the Preferred Choice

Marathon brand components are selected for longevity and minimum maintenance, with special attention given to the selection of high-duty cycle components. Stress engineering provides the optimum degree of structural integrity. Only the best materials are used and the highest standards of quality are observed in the manufacturing process.

Our RamJet[®] **SC**² units are state-of-the-art in roll-off self-contained compactors, featuring large feed openings and expanded container storage capacity. They are designed to optimize safety for workers, store and transport your waste, prevent contamination of public areas in accordance with public health department requirements, improve working conditions for your employees, and reduce disposal costs.

The **SC**² compactor can be customized with a variety of loading arrangements to suit your specific needs.







SC^{2[™]} Features

- New packer head design raises cylinders to a higher parallel position, away from harmful, abrasive waste and liquid.
- V Heavy Duty Wiper and Drag Plate, plus standard ¹/₂" Packer Floor improvements greatly increase the life of the compactor.
- New packer head design has 50% fewer internal hydraulic hoses, which reduces maintenance and repair costs.
- Deck heights of 44" and 48" allow for easy loading from either ground or dock level.
- Clean outs behind the ram and rear cylinder pin access are both easily accessible from outside the compactor body at ground level.
- \checkmark 41 ¹/₂" x 56 ¹/₂" (1041mm x 1473mm) feed opening to handle large, bulky items.
- **v** Continuous feeding capability even while the compactor is operating.
- Adaptable to special loading systems, such as large-capacity hoppers. security chutes, or total enclosures.
- Odor and pest control from the Marathon[®] Ozone Odor Control options.
- **v** Up to 25 tons (22,727 kg) of crushing force to reduce refuse to a fraction of its former size, saving valuable space and reducing your number of hauls.





Perfect for Tipper System Applications

The SC² is the perfect choice for applications requiring a tipper system. Bags of waste are put directly onto the tipper and dumped into the compactor. The self-contained compactor effectively solves spillage and leakage problems associated with conventional stationary compactors and containers.

Some applications require a high degree of security and sanitation. The SC² provides both. Waste is safely stored out of reach of scavengers. Sanitary conditions are enhanced even further with the Marathon Ozone Odor Control System, which destroys odor-producing bacteria by molecular reaction.



Available with Bayne Thinline® Cart Lifter

Equipped with an integral cart lifter, the SC² offers an economical and safety conscious solution for a wide variety of waste material handling applications.

Bayne Thinline[®] cart lifters work with standard 2-bar roll-out carts and can lift up to 750 lbs. Lifter has a powder coated finish so it can stand up to the elements.




The perfect compactor for high volume wet waste

- ▼ Large 40 ¹/₂" x 56 ¹/₂" (1029mm x 1435mm) Feed Opening
- ▼ Full Door Seal with P-Seal
- Bubble Gate with Auto Relatch and Double-Hinge Door
- AR500 Guide Plates
- ▼ Cycon Life-Xtender[™] Cyclic Control

PACTION RAISED TO A HIGHER LEVEL


P-Seal Watertight Closure

The P-shaped Door Seal is specially designed for portable compaction containers to provide a superior watertight closure. The mounting is engineered for quick and easy installation when replacement is necessary, requiring no field fitting, cutting, or welding.



Bubble Gate and Auto Relatch

The innovative "Bubble Gate" adds a full cubic yard to container capacity. Superior compaction ratios result from its special curved shape. These two unique benefits reduce costs of hauling.



nara


R

Double-Hinge with Bronze Bushing

Every **SC**² is tested for watertightness before leaving the factory. Liquid retention is ensured by the incredible Double-Hinge. It creates uniform seal compression while eliminating the seal "scrubbing" and damage so often encountered with competitive designs. The Double-Hinge also saves expensive driver and truck time because only one easy-to-operate ratchet is required to make it work.

Auto Relatch

The ultimate in latch systems, the Marathon[®] brand "Auto Relatch" eliminates the need to hold the door while operating the latch ratchet. This design enables the operator to use both hands on the ratchet, and prevents the door from swinging out inadvertently.



AR500 Guide Plates

The packing ram is supported by an improved abrasionresistant guide system. This exclusive design protects the charge box floor from the full force of the packing ram, extending its life and dramatically reducing compactionrobbing friction.









Improved Fixed Cylinder-Pin Mounting

The redesigned non-rotating cylinders are raised 18" off the floor to move them further away from any accumulated liquid and debris. Fixed cylinder body, plumbing, and pins are housed in the side pockets, eliminating the need for movement or rotation. This redesign also allows for fewer hoses, which reduces maintenance and repair costs.

Rear Access for Quick Cleaning

Open and uncluttered compartment combined with flat floor and quick removal cleaning ports will save time and facilitate more frequent cleaning, extending life of internal components. Newly designed cylinders also allow for easy removal at the rear of the compactor.



Remote Power Pack

Separate from the compactor/container, the sites and free of problems caused by landfill dust. Two simple-to-use, hydraulic quick disconnect fittings couple the power unit to the packing head.


All Marathon Remote Power Packs are built inhouse to our quality standards and each unit must pass a series of stringent tests before it can be shipped with the selected compactor.



Cycon Life-Xtender[™] **Cyclic Control System**

Standard on all SC^{2™} Compactors


- Reliable, solid-state circuitry eliminates all pressure and limit switches
- The Cycon Life-Xtender noshock cycle control extends cylinder and hose wear life
- V Automatic "container full assurance system" - the ram dwells against the load at full pressure, resulting in better compaction
- Smoother running, quieter operation
- Advanced hydraulic design enables the system to operate at minimum pressure levels until the need for more pressure is automatically sensed
- More accurate Advanced Warning or Container Full options
- Dramatically improved cold ∇ weather performance





Optional Doghouse

The optional doghouse offers a totally enclosed charge box with heavy-duty latches, making the machine lockable.



Streamline® Option

The **Streamline** option enables excess liquid to be drained from the container, reducing net payload weight and significantly reducing hauling costs.





Compactor Fundamentals

1

3

4

5

7

?

Eight simple items to consider when choosing the perfect compactor for your application:

- **Recyclables** Is there sufficient volume of recyclable materials to warrant more than one compaction system or is recycling mandatory?
- 2 Size of Waste Is the Feed (Clear Top) Opening large enough to accommodate the largest items without bridging?
 - Safety Standards Does the installation comply with industry ANSI standards? Is there an access interlock switch on chute or hopper doors and gates? Is a "momentary contact" control required?
 - **Power Source** Is adequate power available? Three or single phase?
 - **Convenience** Is the compactor located for easiest use? Loading height? Can a hopper, doghouse, (charge box enclosure) or cart dumping system improve convenience? Can value be added (building or employee security) by loading through the wall? Would an Ozone Odor Control System solve odor or pest control problems?
- 6 Volume of Waste Generated Will the compactor be adequate to handle the volume generated during the peak load periods?
 -) **Location** Does, or can, the waste flow to one central point? Is there an appropriately sized concrete pad for the machine?
- 8 Available Space Is there space for the Compaction System and maneuvering room for collection trucks? Is there adequate overhead clearance? Is there compatibility with the collection truck?
 - Have Questions? If you have any questions or need assistance with your compaction needs, please call **1-800-633-8974** and speak to a specialist. We are here to help!



Dimensions & Specifications




Specifications

Clear Top Opening	40 1/2"L x 56 1/2"W	1,029mm x 1,435mm						
Performance Characteristics								
Cycle Time	37 seconds	37 seconds						
Total Nominal Force	40,300 lbs force	179 kN						
Total Maximum Force	50,000 lbs force	222 kN						
Normal Ram Face Pressure	28.0 psi	193 kPa						
Maximum Ram Face Pressure	34.7 psi	239 kPa						
Ram Penetration	6 ¹ / ₂ "	165mm						
Electrical Equipment								
Electric Motor	10 hp	7.5kW						
208/230/460/575 3-phase	TO IIP							
Service Factor	1.15	1.15						
Electric Control Voltage	120 VAC	120VAC						
Panel Box Assembly								
All Circuits Fused	3-Push Button Station Start/Stop/Reverse							
Hydraulic Equipment								
Hydraulic Pump	13 gpm	49.2 L/min						
Maximum Pressure	2, 050 psi	134 bar						
Hydraulic Cylinders	(2)							
Bore	4"	100mm						
Rod	2 1⁄2"	63mm						
Stroke	47" 1,194mm							

SC² container sides and floors are constructed out of 7 gauge steel plate

SC ²	A	В	C	D	E	Weight
15 Cu. Yd	48"	44"	67"	170 ¹⁵ / ₁₆ "	89"	10,120 lbs.
	1,219mm	1,118mm	1,702mm	4,342mm	2,261mm	4,600 kg
20 Cu. Yd	48"	44"	67"	208 1/16"	89"	10,780 lbs.
	1,219mm	1,118mm	1,702mm	5,285mm	2,261mm	4,900 kg
25 Cu. Yd	48"	44"	67"	214 5/16"	104"	11,290 lbs.
	1,219mm	1,118mm	1,702mm	5,444mm	2,642mm	5,132 kg
30 Cu. Yd	48"	44"	67"	244 ¹³ / ₁₆ "	104"	11,880 lbs.
	1,219mm	1,118mm	1,702mm	6,218mm	2,642mm	5,400 kg
34 Cu. Yd	48"	44"	67"	269 ³ ⁄ ₁₆ "	104"	12,390 lbs.
	1,219mm	1,118mm	1,702mm	6,837mm	2,642mm	5,632 kg
39 Cu. Yd	48"	44"	67"	300 11/16"	104"	13,050 lbs.
	1,219mm	1,118mm	1,702mm	7,637mm	2,642mm	5,932 kg

Pictures and mechanical diagrams in this literature are illustrative only and may not be to scale. Specifications are subject to change without notice in order to accommodate improvements to the equipment. Certified in compliance with ANSI standard Z245.2, all applicable OSHA Regulations. Products must be used only by trained operators in accordance with the Operator Manual, as well as applicable regulations, laws, and ANSI standards.



Dimensions not shown: 8' $5\frac{1}{8}$ " (2,543mm) Overall Width

Ground Roller Widths: 61 ½" (1,569mm) Inside Rollers 67 ½" (1,712mm) Roller Centers 72 ½" (1,851mm) Outside Rollers

Authorized Dealer:

For detailed specifications, recommendations, or free economic studies comparing various systems, contact Marathon® Customer Care at 1-800-633-8974



Compactor & Baler Rental and Leasing Programs Available!

@|2K|

MEMBER

f 🖸 🗘 🛈 💙



Sourcewell

Contract # 041217-MEC

Marathon Equipment Company | P.O. Box 1798 | Vernon, AL 35592-1798

Learn more about Marathon Equipment: 800.633.8974 www.marathonequipment.com