



HI-WAY



Super P Medium-Duty Spreader

Municipalities, contractors and lawn/landscape professionals make the Super P medium-duty spreader their first choice for maximum maneuverability plus workhorse capacity. And when capacity takes priority, take it up a notch with the Super P High Capacity. Advanced features like an inverted V that mounts in fixed position take both to the next level (optional on 8 ft. units).

PRODUCTIVITY FEATURES

- Heavy-duty hopper with 12-gauge sides and ends
- 10-gauge conveyor bottom and sills
- Conveyor system with heat-treated, self-cleaning pintle conveyor chain with 3/8" x 3/4" (.95cm x 1.9cm) chain bars positioned on approximately 5" (12.7cm) centers
- Heavy-duty spinner assembly with six material baffles provides control of the direction and width of spread patterns
- On Super P: 10.5 HP (standard capacity Super P) or 11.0 HP (high capacity Super P) engine with the following in-cab controls: electric engine throttle for in-cab control of engine speed and spread width; electric clutch for stopping and starting conveyor and spinner regardless of engine speed; starter/alternator for in-cab startup of engine and continued recharging of battery while in operation

- Hanging inverted "V" minimizes bridging and reduces pressure on the conveyor (not standard on 8' units)

OPTIONAL FEATURES

- Unpainted 304 stainless steel construction
- 11.0 HP Honda engine drive with in-cab controls or dual hydraulic drive
- Heavy-Duty single piece screen or two-piece flip-up screens are available
- Dual Hydraulic Drive ILO Gas Engine Drive
- Belt-over-chain option is available and intended for use when low application of granular material is needed

Super P						
Length (ft)	Length (m)	Width	Overall Length	Height	Struck Capacity	Approx. Body Weight
8'	2.44	59.5" (151 cm)	115.6" (294 cm)	39" (99 cm)	2.7 yds ³ (2.1 m ³)	895 lbs. (406 kg)
9'	2.74	59.5" (151 cm)	128.0" (325 cm)	39" (99 cm)	3.0 yds ³ (2.3 m ³)	995 lbs. (451 kg)
9' LP*	2.74	59.5" (151 cm)	128.0" (325 cm)	32" (81 cm)	1.9 yds ³ (1.5 m ³)	900 lbs. (408 kg)
9' HC	2.74	80.0" (230 cm)	128.0" (325 cm)	43" (109 cm)	4.03 yds ³ (3.1 m ³)	1105 lbs. (501 kg)
10'	3.05	59.5" (151 cm)	139.6" (355 cm)	39" (99 cm)	3.4 yds ³ (2.6 m ³)	1095 lbs. (497 kg)
10' HC	3.05	80.0" (230 cm)	139.6" (355 cm)	43" (109 cm)	4.4 yds ³ (3.4 m ³)	1205 lbs. (547 kg)
11'	3.35	59.5" (151 cm)	151.6" (385 cm)	39" (99 cm)	3.6 yds ³ (2.8 m ³)	1195 lbs. (542 kg)
11' LP*	3.35	59.5" (151 cm)	151.6" (385 cm)	32" (81 cm)	2.4 yds ³ (1.8 m ³)	1100 lbs. (499 kg)
12'	3.66	59.5" (151 cm)	163.6" (416 cm)	39" (99 cm)	3.9 yds ³ (3.0 m ³)	1295 lbs. (587 kg)

Note: Super P High Capacity requires a minimum GVWR of 20,000 lbs.

* LP = Low Profile

