



# Ampliroll® 18,000 POUNDS

## 95 SERIES



### Why buy a HookLift?

Do you have trucks that are not always being used?  
Do you have a difficult time finding quality drivers?  
Is there a piece of equipment you could use,  
but can't justify adding another truck?

**It's Multi-tasking for your truck.  
The possibilities are Infinite.**

With an Ampliroll® you can do just about anything.

**Deliver Load Dump**

### FEATURES

- **Sliding Jib** gives you greater range of body body lengths and optimal weight distribution.
- **Twin Pivot** allows you to dump a uniform pile of material.
- **Dual Cylinders** gives greater stability while dumping and loading.
- **Safely** operated from the drivers seat.
- **Dock Level** loading and unloading
- **Double** your payload by pulling another body on a trailer.
- **Maneuverable** to operate, the container can be loaded within a **60 degree** arc.
- **Spot** the container exactly where you want it, by pushing it into place with no damage
- **Quickly** loads a body in less than one minute.
- **Investment** that will outlast your truck, Amplirolls® will last over **25 years**.
- Meets all highway safety standards.

The Ampliroll Hook Lift was invented in 1969. Our process of laser cutting and robotic welding enables us to provide you with a complete line of hooklifts, that eliminate the use of **SHIMS** and **WEAR PADS**.

**Ampliroll® has been imitated  
but never duplicated.  
Compare the difference before you buy.**



Ampliroll Model	AL 95SS-12	AL 95S-15	AL 95L-16
<b>Actual Lifting Capacity</b> (including container)	18,000 lbs.	18,000 lbs.	18,000 lbs.
<b>Shipping Weight</b>	2408 lbs.	2408 lbs.	2417 lbs.
<b>Dump Angle</b>	54 degrees	54 degrees	54 degrees
<b>Cab to Axle</b>	96 to 120 inches	120 to 138 inches	126 to 150 inches
<b>Over all length</b>	146 inches	162 inches	174 inches
<b>Body Length</b>	10 to 13 feet	10 to 16 feet	11 to 17.5 feet
<b>Hydraulic Specifications:</b>			
Pump - 1.53 displacement gear pump operating at 4200 psi			
Controls - cable operated valve			
Reservoir - 12 gallons			
Filter - 10 micron, return line with replaceable cartridge			
Maximum operating pressure - 4,200 psi			
Hoses, tubes & fittings all JIC/SAE specifications			
<b>Steel: Special Alloy</b>	<b>ASTM A 572</b> in jib, central arm and tilting frame		
<b>Safety Devices:</b>	Safety valve prevents jib operation during dump mode. Counter-balance valve to hold cylinder if hose breaks. Automatic locking device for dump mode. Slide through container locks.		
<b>Truck Requirements:</b>	GVWR - 19,500 to 26,000 lbs Front Axle capacity - 6,000 to 8,000 lbs Rear Axles capacity - 15,000 to 18,000 lbs		

**Notice:** Longer containers may not comply with I.C.C. bumper regulations and can effect dump angle.



# Marrel

## Corporation

4750 14 Mile Road  
 Rockford, MI 49319  
 Phone: 616-863-9155  
 Fax: 616-863-9177  
 Toll Free: 866-822-3580  
 email: [equipment@amplirollusa.com](mailto:equipment@amplirollusa.com)  
[www.amplirollusa.com](http://www.amplirollusa.com)

Distributed by:

