



XT3 Type I

Multi-Purpose Dump Body

Hi-Way XT3 Type I Front or Rear Discharge Multi-Purpose Dump Body

1. Spreads- Broadcast deicing materials at rear or at front with front cross conveyor.
2. Hauls- Flat dump body floor allows hauling of virtually anything, including pallets & barrels.
3. Dumps- Front telescopic hoist provides low center of gravity.

Low Maintenance Features

- Heavy-duty 7-gauge 409 stainless steel inner and outer longitudinal sills are fully welded to body floor to resist corrosion and improve strength.
- 7-gauge grade 50 body sides feature one-piece construction with radius design to reduce material build-up. Sloped top rails on side sheets and headsheets add body support and prevent debris build-up on the rails.
- 3/16" (.48cm) AR400 conveyor floor resists bending from load impact and provides superior wear resistance.
- High torque 25:1 gear case starts even the heaviest loads. Includes idler with shafts, sprockets and bearing that remove as one assembly to simplify maintenance. Dropped forged steel sprockets ensure longer life.

High Productivity Features

- Quick detach front and/or rear spinner assemblies adjust up/down, side to side, and fore/aft for precise spread pattern control.
- For front discharge a 16.9" (42.9cm) wide cross conveyor handles larger capacity than auger feed or chute style front discharge units.

Optional Equipment

- High volume liquid storage for pre-wet or anti-icing
- Unpainted 201 or 304 stainless steel construction for added resistance to corrosion.
- Pre-wet system, screens, ladder, and conveyor cover are just some of the other options available.


XT3 Type I						
Length (ft)	Length (m)	Width	CA/CT*	Struck Capacity	Struck Capacity w/ Sideboards	Approx. Body Weight
9'/10'	2.74/3.05	95.5" (243 cm)	84" (213 cm)	6.4 yds ³ (4.89 m ³)	9.7 yds ³ (7.42 m ³)	4025 lbs. (1826 kg)
10'/11'	3.05/3.35	95.5" (243 cm)	96" (244 cm)	7.2 yds ³ (5.50 m ³)	10.8 yds ³ (8.26 m ³)	4215 lbs. (1912 kg)
11'/12'	3.5/3.66	95.5" (243 cm)	108" (274 cm)	8.0 yds ³ (6.12 m ³)	12.0 yds ³ (9.17 m ³)	4405 lbs. (1998 kg)
12'/13'	3.66/3.96	95.5" (243 cm)	108" (274 cm)	8.8 yds ³ (6.73 m ³)	13.2 yds ³ (10.09 m ³)	4595 lbs. (2084 kg)
13'/14'	3.96/4.27	95.5" (243 cm)	120" (305 cm)	9.7 yds ³ (7.42 m ³)	14.5 yds ³ (11.09 m ³)	4785 lbs. (2170 kg)
14'/15'	4.27/4.57	95.5" (243 cm)	132" (335 cm)	10.5 yds ³ (8.03 m ³)	15.6 yds ³ (11.93 m ³)	4975 lbs. (2257 kg)

*The Cab to Axle/Tandem dimensions are only guidelines. Consult federal, state and local weight laws and chassis manufacturer's ratings to ensure neither government weight restrictions, nor GVWR and GAWRs are exceeded.



Spinner / Conveyor

The rear spinner assembly adjusts up/down, side to side, and fore/aft for precise spread pattern control.



Hoist

Front telescopic hoist provides lower center of gravity when dumping. Cylinder includes 2-year warranty.



Body

95.5" (243cm) wide body provides maximum capacity. Body side sheet and floor feature one-piece construction.



Optional SB3 Sandbag Filler Attachment

- Constructed of 304 stainless steel and retrofits onto any existing XT3 Type I or III with rear discharge set-up.
- Capable of filling two 50-pound sandbags in 10 seconds.
- Offers quick and easy installation and removal.
- Features an adjustable vertical chute to accommodate varying truck heights and bag sizes as well as an adjustable 12-volt DC vibrator, which can be turned on and off with an optional control, to aid in the flow of sand through the chute.

Products and specifications subject to change without notice. Photos and illustrations may or may not include optional equipment. Hi-Way® is a registered trademark of New Leader Manufacturing. HWXT3-I-2019-01