



# XT3 Type III Multi-Purpose Dump Body

## Hi-Way XT3 Type III Rear Discharge Multi-Purpose Dump Body

1. Spreads- Broadcast deicing materials at rear.
2. Hauls- Flat dump body floor allows hauling of virtually anything, including pallets and barrels.
3. Dumps- Front telescopic hoist provides low center of gravity.

### Low Maintenance Features

- Heavy-duty 7-gauge 409 stainless steel inner and outer longitudinal sills are fully welded to body floor to resist corrosion and improve strength.
- 7-gauge grade 50 body sides feature one-piece construction with radius design to reduce material build-up. Sloped top rails on side sheets and headsheets add body support and prevent debris build-up on the rails.
- 3/16" (.48cm) AR400 conveyor floor resists bending from load impact and provides superior wear resistance.
- High torque 25:1 gear case starts even the heaviest loads. Includes idler with shafts, sprockets and bearing that remove as one assembly to simplify maintenance. Dropped forged steel sprockets ensure longer life.

### High Productivity Features

- Quick detach front and/or rear spinner assemblies adjust up/down, side to side, and fore/aft for precise spread pattern control.

### Optional Equipment

- High volume liquid storage for pre-wet or anti-icing
- Unpainted 201 or 304 stainless steel construction for added resistance to corrosion.
- Tool boxes, stainless underbody pan, pre-wet system, screens, ladder, and conveyor cover are some of the other options available.



# HI-WAY XT3 Type III

XT3 Type III						
Length (ft)	Length (m)	Width	CA/CT*	Struck Capacity	Struck Capacity w/ Sideboards	Approx. Body Weight
10'	3.05	95.5" (243 cm)	84" (213 cm)	7.6 yds <sup>3</sup> (5.81 m <sup>3</sup> )	11.2 yds <sup>3</sup> (8.56 m <sup>3</sup> )	4323 lbs. (1961 kg)
11'	3.35	95.5" (243 cm)	96" (244 cm)	8.4 yds <sup>3</sup> (6.42 m <sup>3</sup> )	12.4 yds <sup>3</sup> (9.48 m <sup>3</sup> )	4513 lbs. (2047 kg)
12'	3.66	95.5" (243 cm)	108" (274 cm)	9.2 yds <sup>3</sup> (7.03 m <sup>3</sup> )	13.6 yds <sup>3</sup> (10.40 m <sup>3</sup> )	4703 lbs. (2133 kg)
13'	3.96	95.5" (243 cm)	108" (274 cm)	10.0 yds <sup>3</sup> (7.65 m <sup>3</sup> )	14.7 yds <sup>3</sup> (11.24 m <sup>3</sup> )	4893 lbs. (2219 kg)
14'	4.27	95.5" (243 cm)	120" (305 cm)	10.9 yds <sup>3</sup> (8.33 m <sup>3</sup> )	16.0 yds <sup>3</sup> (12.23 m <sup>3</sup> )	5083 lbs. (2306 kg)
15'	4.57	95.5" (243 cm)	132" (335 cm)	11.7 yds <sup>3</sup> (8.95 m <sup>3</sup> )	17.1 yds <sup>3</sup> (13.07 m <sup>3</sup> )	5273 lbs. (2392 kg)

\*The Cab to Axle/Tandem dimensions are only guidelines. Consult federal, state and local weight laws and chassis manufacturer's ratings to ensure neither government weight restrictions, nor GVWR and GAWRs are exceeded.



## Pre-Wet System

Liquid is blended into material prior to discharge onto the spinner through chain conveyor system.



## Spinner

The rear spinner assembly adjusts up/down, side-to-side, and fore/aft for precise spread pattern control.



## Hoist

Front telescopic hoist provides lower center of gravity when dumping. Cylinder includes 2-year warranty.



## Body

95.5" (243cm) wide body provides maximum capacity. Body side sheets and floor feature one-piece construction.

Products and specifications subject to change without notice.  
Photos and illustrations may or may not include optional equipment.  
Hi-Way® is a registered trademark of Highway Equipment Company, Inc., d/b/a New Leader Manufacturing.  
© 2019 Highway Equipment Company, Inc., d/b/a New Leader Manufacturing.  
HWXT3-III-2019-01